


















PAP Unit	Therapy Needs		Comfort Features			Convenience			Physical Characteristics	
Model	Type of PAP	Clinical Data Collection	Inspiratory or Expiratory Comfort	Leak Compensation/Alert	Humidifier	Humidifier/Chamber Features	Remote Update of Pressure Setting	Patient Reminder System	Power Source	Weight
 REMstar Auto M with A-Flex	Auto-adjusting	Encore Pro via SmartCard + reader	A-Flex or C-Flex	Leak compensation, plus mask off alert	Optional 	Humidifier chamber comes apart easily & is dishwasher safe (top rack). Hidden, easy to fill, & stainless steel base.	Yes with SmartCard	Mask & filter replacement + service due date + supplier call	Intl. power supply. Used with direct DC adapter cord.	1 kg (does not include humidifier) (325 ml)
 S8 AutoSet II	Auto-adjusting	ResScan 3.5 software via ResScan data card + reader+Reslink	EPR with Easy-Breathe	Leak compensation, plus mask off alert	Optional 	Humidifier temperature adjusts to room temperature. Spill back protection.	Yes with ResScan data card	Mask & filter replacement + service due date + supplier call	Intl. power supply. Designed for use with DC/AC converter.	1.4 kg (does not include humidifier) (385 ml)
 REMstar Auto M	Auto-adjusting	Encore Pro via SmartCard + reader	C-Flex	Leak compensation, plus mask off alert	Optional 	Humidifier chamber comes apart easily & is dishwasher safe (top rack). Hidden, easy to fill, & stainless steel base.	Yes with SmartCard	Mask & filter replacement + service due date + supplier call	Intl. power supply. Used with direct DC adapter cord.	1 kg (does not include humidifier) (325 ml)
 SleepStyle 200 Auto	Auto-adjusting	Performance Maximizer software, SmartStick	SensAwake Technology	Leak compensation, plus mask off alert	Built-in	Auto-adjusting humidification plus integrated heated tube. Low cost chamber , replaced bi-annually.	Yes with SmartStick	N/A	Intl. power supply. Designed for use with DC/AC converter.	1.9 kg with chamber (400 ml)
 REMstar Pro M	Fixed Pressure	Encore Pro via SmartCard + reader	C-Flex	Leak compensation, plus mask off alert	Optional 	Humidifier chamber comes apart easily & is dishwasher safe (top rack). Hidden, easy to fill, & stainless steel base.	Yes with SmartCard	Mask & filter replacement + service due date + supplier call	Intl. power supply. Used with direct DC adapter cord.	1 kg (does not include humidifier) (325 ml)
 S8 Elite II	Fixed Pressure	ResScan 3.5 software via ResScan data card + reader	EPR with Easy-Breathe	Leak compensation, plus mask leak alert	Optional 	Spill back protection and stainless steel base.	Yes with ResScan data card	Mask & filter replacement + service due date + supplier call	Intl. power supply. Designed for use with DC/AC converter.	1.4 kg (does not include humidifier) (385 ml)
 SleepStyle 600 (HC604)	Fixed Pressure with Integrated Humidifier	Compliance Maximizer software, direct download	N/A	N/A	Built-in	Auto-adjusting humidification plus integrated heated tube. Low cost chamber , replaced bi-annually.	N/A	N/A	Intl. power supply. Designed for use with DC/AC converter.	2.1 kg with chamber (600 ml)
 REMstar M	Fixed Pressure	Therapy meter	N/A	N/A	Optional 	Humidifier chamber comes apart easily & is dishwasher safe (top rack). Hidden, easy to fill, & stainless steel base.	N/A	N/A	Intl. power supply. Used with direct DC adapter cord.	1 kg (does not include humidifier)
 S8 Escape	Fixed Pressure	ResScan 3.5 software via ResScan data card + reader (compliance only)	N/A	N/A	Optional 	Spill back protection and stainless steel base.	N/A	Mask & filter replacement + service due date + supplier call	Intl. power supply	1.3 kg (does not include humidifier)
 SleepStyle 200 HC233	Fixed Pressure with Integrated Humidifier	N/A	N/A	N/A	Built-in	Auto-adjusting humidification. Low cost chamber , replaced bi-annually.	N/A	N/A	Intl. power supply. Designed for use with DC/AC converter.	1.8 kg with chamber (400 ml)